

Crown Wallcare (Acrylic) Putty

PRODUCT DESCRIPTION

Type: A copolymer based high build paste

Recommended use: Base coat to cover unevenness and pinholes on interior surfaces

Substrates: Plasterwork, Boards and Timber

Advantages: Highly flexible. Supplied ready for use – no mixing required.

PRODUCT DATA:

Colour Range: White

Pack Sizes: 5kg, 20kg and 30kg

Finish: Matt and smooth when sanded with fine abrasive paper.

Thinner & equipment cleaner: Water

Dilution Ratio: Wallcare is supplied ready for use but can be thinned with emulsion paint if surface is to be painted in emulsion paint. This will eliminate any graining.

Drying Times: Surface dry: 2 hours. Hard dry: Overnight

APPLICATION DATA:

The product can be applied by: Steel trowel or spatula

Spreading Capacity per coat: Depends on film thickness applied, type of texture, surface porosity, imperfections, temperature & wastage during painting.

Difficult to approximate but roughly $\frac{1}{4}\text{m}^2$ to 2m^2 per kg.

TECHNICAL DATA SHEET



Surface preparation & Application:

Surface	Preparation	Application
New Plaster, gypsum or wood surface	Brush out any loose dust, chalk, grease, fungi, algae and old paint flakes followed by water jetting if required. Fill up all major cracks and defects with cement and sand mixture Wallcare Putty should be applied over fully cured surface, not recommended to use over pre- painted surface.	Apply Wallcare Putty from bottom to upward direction uniformly with the help of a steel trowel/putty blade to ensure less wastage. Allow the surface to dry at least for 2 hours. After drying of first coat rub the surface very gently with the putty blade to remove loose particles. Apply the 2 nd coat after the 1 st is fully set. Leave to dry overnight. The total thickness of the coats should not exceed 2 mm. Sand smooth with P320 grit paper and then apply topcoat

Availability: From Crown Depots in Nairobi, Kisumu, Mombasa, Meru, Nyeri, Eldoret, Arusha, Mwanza, Dar es Salaam, Kigali and through Crown Stockists.

Storage Conditions: Store under cool dry conditions away from direct sunlight, heat and extreme cold.

Disclaimer: The recommendations contained herein are given in good faith and meant to guide the user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable. No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond Crown Paints Kenya PLC control.

Technology may change with time, necessitating changes to this Technical Data Sheet (TDS).

Crown Paints Kenya PLC reserves the right to amend the TDS without any further notice.

It is the responsibility of the user to ensure that the latest TDS is being used for reference.



For additional health & safety information, please refer to our Material Safety Data Sheet (MSDS)