

Crown Paints Kenya PLC

Head Office Likoni Road PO Box 78848 - 00507 Nairobi, Kenya Tel: +254 -20- 2165703/4/6 Or: +254 -20- 6533604-12 Fax: 6558480 / 6550712 www.crownpaints.co.ke

December 2018

MATERIAL SAFETY DATA SHEET

1. Substance and Company Identification

Product Name: Crown Rockfast Hi-Build Texture Finish, all

colours

Chemical Family: Water based Textured Paint

Manufacturer: Crown Paints Kenya PLC, Mogadishu Road,

Industrial Area, Box 78848-00507, Nairobi, Tel:

+254-20-533603, Fax: +254-20-544641

Email: safety @crownpaints.co.ke; OR

technical@crownpaints.co.ke

2. Composition, Information and Ingredients

<u>Weight %</u>
10 - 20
70 - 90
10 - 20
0.5 - 2

3. Hazard Identification

No significant hazards. Ammonia (<1%) can cause choking when inhaled.

4. First aid measures

Eyes: Immediately flush eyes thoroughly with plenty of water for 15 minutes to remove particulates. If burning, redness, itching, pain or other symptoms persist or develop, call physician.

Skin: Rinse with water until free of material to avoid abrasions, then wash skin thoroughly with soap and water. If irritation persists, consult physician.

Inhalation: Remove subject to fresh air. If respiratory symptoms persist (irritation, cough, nausea, dizziness, etc.), consult physician.

Ingestion: No specific recommendation. Call physician.

5. Fire fighting measures

This is a non-flammable liquid.



Crown Paints Kenya PLC

Head Office Likoni Road PO Box 78848 - 00507 Nairobi, Kenya Tel: +254 -20- 2165703/4/6 Or: +254 -20- 6533604-12 Fax: 6558480 / 6550712 www.crownpaints.co.ke

Suitable extinguishing media: Carbon dioxide (CO₂) or universal

aqueous film forming foam

Flash point: >100°C

6. Accidental Release Measures

Personal: Provide ventilation. Remove sources of ignition

Environmental: Do not flush into surface water or sanitary sewer

systems

Clean up: Soak with inert material (e.g., sand, silica gel, acid binder, sawdust) and place in clean, empty containers for disposal. Dispose in accordance with the regulations.

7. Handling and Storage

Handling: Vapour may collect on low areas. Avoid breathing mist when Spray applying or dust when sanding.

Storage: Store at temperatures between 1 and 40°C in a dry place. Protect from extreme heat and exposure to direct sunlight. Keep container tightly closed.

8. Physical and Chemical Properties

Appearance Thick paste pH 8-10

Specific gravity 1.5-2.5

Viscosity Very thick
% volatile < 2%

Odour Mild

9. Chemical stability and reactivity

This product is stable and will not undergo hazardous reactions. Avoid storage and using in temperatures below 1 and above 40°C. When heated to decomposition it emits acrid smoke and irritating fumes.

10. Toxicological information

Product has no toxicity or carcinogenic effect on human beings.

11. Ecological information

Environmental toxicity: Product has no known adverse effect on the ecology. Do not allow large undiluted quantities directly into waterways.

12. Transport information



Crown Paints Kenya PLC

Head Office Likoni Road PO Box 78848 - 00507 Nairobi, Kenya Tel: +254 -20- 2165703/4/6 Or: +254 -20- 6533604-12 Fax: 6558480 / 6550712 www.crownpaints.co.ke

Not classified or regulated as a hazardous material according to transport regulations but precautions should be taken to avoid freezing during transportation.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Incinerate in approved facility. Do not incinerate closed container. Dispose in accordance

With Federal, State/Provincial, and Local regulations regarding pollution.

14. Transport information

Not classified or regulated as a hazardous material according to transport regulations but precautions should be taken to avoid freezing during transportation.

15. REGULATORY INFORMATION

TSCA Certification

All Chemicals in this product are listed, or are exempt from listing on the TSCA Inventory.

16. OTHER INFORMATION

Further information

The information provided I this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, storage, transportation, disposal and release and is not to be considered a warranty. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials unless specified in the text.

-----XXX-----